

RHY

TOP-330-PLUS-2 spot varnish and die cutting



Machine for cost-efficient, high quality converting and finishing. Features winding, cold foiling, super varnishing, Semi or full flexo printing, semi- or full rotary die cutting, IML system, slitting and sheeting. The optimal solution for high productivity. Fully servo driven.

TOP-330-PLUS-2	OPTION WIDTH 420MM/520MM
Max Web Width	330 mm
Max Die-cutting speed (full-rotary)	110m/ mim
Max Die-cutting Speed (semi-rotary)	60 m/min
Max Flexo Printing Speed (full-rotary)	90 m / min
Max Flexo Printing Speed (semi-rotary)	60 m / min
Accuracy of Flexo Register	±0.15 mm
Max Unwinder dia.	700 mm
Max Rewinder dia.	700 mm
Min Slitting width	16 mm
Accuracy of Adhesive Cutting	±0.15 mm
Accuracy of IML Cutting	±0.25 mm
Total Motor Power	19 KW ~ 21 KW
Registration	Mark Sensor
Dimension	3650×1260×2025 mm
Weight	3600 KGS



user-interface. Optional further

automation and razorblades.

rewind.

COLD FOIL & SUPER VARNISH Cold-foil and super varnish with two pneumatic shafts and unwind/





REWINDING OPTIONS

Standard single rewind. Upgrade to dual rewind, or a productive Turret with buffer and automatic cutting of the web for optimal productivity