Frimpeks UV Curable Flexo Inks

A newly developed ink series for flexible packaging, self-adhesive labels and wrap-around labels.

Product Range:

Process inks, base colors, PANTONE® inks are available. Special hues are available on request.

Technical Details:

- good adhesion on a wide range of synthetic materials such as paper and cartonboard
  for synthetic materials surface tension of 38-42 dyne/cm is requied to obtain optimum adhesion
- low odor
- solvent free
- fast curing (high reactivity)
- very good runnability
- suitable for varnishing and hot foil stamping
- suitable for printing on thermal-papers

Remark:
Before beginning to print we recommend pretests, in order to test the desired characteristics of the finished product.

Printing Details:

Printing Speed: Up to 150 m/min
Anilox Volume:

900/1200 CPI	Process Colors Ultra 32000-N	2.3-3 cm3/m2 (1.5-2.0 BCM)
700/900 CPI	Process Colors Extra 31000-N	3-4 cm3/m2 (1.9-2.5 BCM)
250/550 CPI	Solid Colors	5-10 cm3/m2 (3.5-6 BCM)

Packaging:

Standard Packaging: 5 KG buckets

Technical Service:

Kindly note that we are ready at any time for competent technical application support on your site.
Please contact our technical staff for printing inks:
uv@frimpeks.com

Storage:

Optimal Storage Conditions
The optimal storage temperature is between 5°C to 25°C.
Higher storage temperatures reduce the shelf-life.

Remark:
- protect from frost
- store in a cool and dark place
- stir well before use
- the lid must be closed immediately after usage

Warranty:
If the inks are stored correctly, we guarantee a shelf life of 12 months from date of production.
However, we know from practical experience that the inks can remain usable for longer periods if they are properly handled and stored.

Cleaning:

We recommend using ester and ketone resistant rollers (EPDM-material).
The inking roller, anilox roller and printing plate have to be resistant against UV based inks and detergents (see manufacturer's instructions).

Disclaimer:
The statements listed on this publication are according to our best knowledge. The statements do not exonerate the user from their own responsibility to determine that our products are suitable for their processes. They are intended to inform and advise and are subject to influence from the technical process.
This edition of June 15, 2020 replaces all previous editions. With the present edition all older editions are null and void

Frimpeks Kimya ve Etiket Sanayi Ticaret A.S.
Hacıseremet Mevkii Sanayi Bölgesi Barajyolu 4/93 No:53, Velimese 59850 Tekirdag/ Turkey
T. +90 282 674 5200 - F. +90 282 674 4353 - frimpeks.com - uv@frimpeks.com

Technical Information

Frimpeks UV Curable Flexo Inks

		Lightfastness	Alkali	Solvent
Type	**Product Denomination**	**According to ISO 105 B01 specification**	**According to ISO 2838 specification**	**According to ISO 2837 specification**
		1 to 8 blue scale 8-Excellent / 1-Poor	1 to 5 5-Excellent / 1-Poor	1 to 5 5-Excellent / 1-Poor
Process Color Ultra-N	Pr. Yellow	4/5	5	4/5
Process Color Ultra-N	Pr. Magenta	4/5	2	3
Process Color Ultra-N	Pr. Cyan	7	5	5
Process Color Ultra-N	Pr. Black	7	5	5
Process Color Extra-N	Pr. Yellow	4/5	5	4/5
Process Color Extra-N	Pr. Magenta	4/5	2	3
Process Color Extra-N	Pr. Cyan	7	5	5
Process Color Extra-N	Pr. Black	7	5	5
Base Color	Yellow	4/5	5	4/5
Base Color	Yellow LF	6	5	4
Base Color	Orange	5	5	4
Base Color	Warm red	3	2	3
Base Color	Mid red (032)	5	5	3/4
Base Color	Rubine Red XT	4/5	2	3
Base Color	Rubine Red LF	6/7	5	5
Base Color	Rhodamine red	3/4	2	2
Base Color	Rhodamine red LF	7	5	5
Base Color	Purple	4	2	2
Base Color	Violet	4	2	2
Base Color	Violet LF	7	5	5
Base Color	Reflex blue LF	7	5	5
Base Color	Blue XT	7	5	5
Base Color	Green	7	5	5
Base Color	Mixing Black	8	5	5
	Transparent White			
	Opaque White	8	5	5

Disclaimer:
The statements listed on this publication are according to our best knowledge. The statements do not exonerate the user from their own responsibility to determine that our products are suitable for their processes. They are intended to inform and advise and are subject to influence from the technical process.
This edition of June 15, 2020 replaces all previous editions. With the present edition all older editions are null and void

Frimpeks Kimya ve Etiket Sanayi Ticaret A.S.
Hacıseremet Mevkii Sanayi Bölgesi Barajyolu 4/93 No:53, Velimese 59850 Tekirdag/ Turkey
T. +90 282 674 5200 - F. +90 282 674 4353 - frimpeks.com - uv@frimpeks.com

Frimpeks UV Curable Flexo Inks

Marking:

Marking according to EU legislations:
Our inks are fully adhering to regulations such as Reach, 1272/2008 CLP, 453/2010 EU, ROHS III Directive 2015/863, and/or 528/2012 EU regulations.
All material safety data sheets (MSDS) are available on request.

Declaration of Composition and Product Declaration:

CEPE / EuPIA – Exclusion List
CEPE is the European Council of producers and importers of paints, printing inks and artists colours whereas EuPIA is the European Printing Ink Group of CEPE. The printing ink industry voluntarily came up with the Exclusion List for specific substances many years ago. The raw materials used by Frimpeks for the formulation of our printing inks/varnishes meet the guidelines of the CEPE / EuPIA Exclusion.

Heavy Metals
CONEG stands for Coalition of North-Eastern Governors in the USA. One of their legislations, adopted by 18 states as of 1998, requires reductions in the amount of the four heavy metals mercury, lead, cadmium, and hexavalent chromium in packaging and packaging components sold or distributed in their member states. For Frimpeks printing inks/varnishes the limits for heavy metals as listed in the CONEG-Regulation (USA) are met. The Euro Norm 71.3 refers to the max level of heavy metals in children's toys. For Frimpeks printing inks/varnishes, the limits for heavy metals as listed in the DIN EN 71-3:2019 are met.
Heavy metals are no part of our formulations.

Hazardous Substances
Substances mentioned in the Directive 2015/863 known as RoHS III are not intentionally used in our formulations printing inks/lacquers

SVHC-substances (substances of very high concern):
In our products no substances are used which meet the criteria of SVHC-substances (substances of very high concern). SVHC-substances are substances which are classified as CMR 1 & 2, PBT (PBT pollutants are chemicals that are toxic, persist in the environment and bioaccumulate in food chains), vPvB (Substances that are potentially very persistent and very bioaccumulative) and endocrine disruptors (artificial hormones).

The substances listed in the guide line 67/548/EEC (amended by the directive 2006/121/EC) and in the guide line 76/769/EEC are not part of the formulation of our printing inks/lacquers. Furthermore, we confirm that our printing inks/lacquers are in accordance with the EC regulation 1895/2005 (repeals the guide line 2002/16/EC).

Enhanced Statement of composition (ESoC) is available on request to support with migration testing and compliance with Plastics Regulation (EU) No 10/2011, the Swiss Ordinance 817.023.21 Annex 1 or 6 or listed on the 'Provisional List of Additives used in Plastics' or listed as a food additive in Regulation (EC) No 1333/2008 and Regulation (EC) 1334/2008.

Food Contact
Extra and Ultra series intended for use on secondary food packaging in indirect contact scenarios. The Packaging made with this inks and coating series is definitely not suitable for direct food contact. The general food packaging safety 'framework' Regulation (EC) No 1935/2004 of the European Parliament (Materials and articles intended to come into contact with food). This regulation refers specifically to food contact materials and articles rather than to inks and associated coatings. A more detailed secondary food contact declaration is available on request.

Quality Assurance:

ISO 9001
The production site of Frimpeks is certified according to DIN EN ISO 9001:2015 and DIN EN ISO 14001:2005 (corresponds to EN ISO 14001 edition 2009).

Disclaimer:
The statements listed on this publication are according to our best knowledge. The statements do not exonerate the user from their own responsibility to determine that our products are suitable for their processes. They are intended to inform and advise and are subject to influence from the technical process.
This edition of June 15, 2020 replaces all previous editions. With the present edition all older editions are null and void

Frimpeks Kimya ve Etiket Sanayi Ticaret A.S.
Hacıseremet Mevkii Sanayi Bölgesi Barajyolu 4/93 No:53, Velimese 59850 Tekirdag/ Turkey
T. +90 282 674 5200 - F. +90 282 674 4353 - frimpeks.com - uv@frimpeks.com